

IN THE ABSTRACT:

Please amend the Abstract as indicated below:

A gated clock recovery circuit is disclosed that receives an input data stream and
5 generates a frequency and phase aligned clock output. The gated clock recovery circuit
substantially instantaneously adjusts the generated clock signal to phase changes in the incoming
data stream. In addition, the gated clock recovery circuit generates the clock output signal using
only transmitted non-predetermined data. The gated clock recovery circuit includes two PLL
circuits. The first PLL (PLL1) adjusts to the frequency of the transmitter, and provides a bias
10 voltage, CAP1, to the second PLL (PLL2) to indirectly initially tune the second PLL (~~PLL2~~). The
bias voltage, CAP1, is applied to the second PLL (~~PLL2~~) through a transmission gate (or switch)
that is initially in a closed (short) position. Thus, the first PLL (~~PLL1~~) drives the bias voltage,
CAP2, of the second PLL (~~PLL2~~), to align the frequency with the transmitter, until received data
opens the transmission gate. Thereafter, the bias voltage, CAP2, is removed and the second PLL
15 (~~PLL2~~) can operate without being controlled by PLL1 so that the second PLL (~~PLL2~~) oscillates in
phase with the received data. Simultaneously, the received data starts the oscillator in the second
PLL (~~PLL2~~) so that the second oscillator is in phase with the received data. The second PLL
(~~PLL2~~) then maintains this phase relationship between the second oscillator and the received data.